

P/N MS9519-09

Military-Fasteners.com

Description

Fastener Length: 11/16", Thread: 1/4-28, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS951909	
Minimum Qty (MOQ):	10 EA	
NSN:	5306-01-220-3444	
Schedule B:	7318.15.8085	
ECCN:	EAR99	
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)	



P/N MS9519-09 Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.579 Inches Minimum And 0.619 Inches MaximumFastener Length:0.678 Inches Minimum And 0.698 Inches MaximumHead Style:HexagonHead Height:0.146 Inches Minimum And 0.166 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.166 Inches MaximumNominal Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Steel Comp 8740 OverallMaterial Document And Classification:Ams 24200 Assn Std Single Material Response OverallSurface Treatment:Codmium Overall Surface Treatment Response OverallThread Series Designator:Unif		
Thread Length:0.579 Inches Minimum And 0.619 Inches MaximumFastener Length:0.678 Inches Minimum And 0.698 Inches MaximumHead Style:HexagonHead Height:0.146 Inches Minimum And 0.166 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Stel Comp 8740 OverallMaterial:Mes 322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Thread Class:	За
Fastener Length:0.678 Inches Minimum And 0.698 Inches MaximumHead Style:HexagonHead Height:0.146 Inches Minimum And 0.166 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.146 Inches Minimum And 0.166 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Hardness Rating:6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Thread Length:	0.579 Inches Minimum And 0.619 Inches Maximum
Head Height:0.146 Inches Minimum And 0.166 Inches MaximumWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Width Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Stel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Material:	Head Style:	Hexagon
Nomial Thread Diameter:0.250 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:28Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Head Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Features Provided:Finished HeadFinished Quantity Per Inch:28Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Thread Quantity Per Inch:28Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Features Provided:	Finished Head
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:32.0 Microinches ThreadsMaterial Document And Classification:Steel Comp 8740 OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Thread Quantity Per Inch:	28
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:32.0 Microinches ThreadsMaterial Document And Classification:Steel Comp 8740 OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Steel Comp 8740 Overall Material Document And Classification: Ams 6322 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Ams 6322 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall	Surface Finish:	32.0 Microinches Threads
Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall	Material:	Steel Comp 8740 Overall
Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall	Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
	Surface Treatment:	Cadmium Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
	Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS9519-09</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.