

Description

Fastener Length: 1-3/4", Thread: 1/4-28, Thread Length: 51/64", MS9519 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS951926 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-00-177-5570 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS9519-26 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Length: | 0.750 Inches Minimum And 0.810 Inches Maximum |
| Fastener Length: | 1.750 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.156 Inches Nominal |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.940 Inches Minimum And 1.000 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Ams 2400 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9519-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.