

P/N MS9532-04

Military-Fasteners.com

Description

Fastener Length: 5/8", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS953204
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-301-3752
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N MS9532-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.527 Inches Minimum And 0.547 Inches Maximum
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Hexagon
Head Height:	0.219 Inches Minimum And 0.229 Inches Maximum
Width Between Flats:	0.631 Inches Minimum And 0.641 Inches Maximum
Hole Diameter:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.088 Inches Minimum And 0.108 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams6322 Mil Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms9532 Government Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS9532-04</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.