



Military-Fasteners.com

P/N MS9555-02

Description

Fastener Length: 5/16", Thread: 8-36, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS955502 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-173-8117 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS9555-02 Specifications

| | |
|-----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.220 Inches Minimum And 0.260 Inches Maximum |
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.220 Inches Minimum And 0.240 Inches Maximum |
| Width Between Flats: | 0.219 Inches Nominal |
| Extended Washer Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Extended Washer Thickness: | 0.030 Inches Minimum |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 36 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum |
| Screw Material: | Iron Alloy 660 |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.