

P/N MS9555-03

Description

Fastener Length: 5/16", Thread: 8-36, Thread Length: 15/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS955503

Minimum Qty (MOQ): 10

NSN: 5305-00-173-8117

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



P/N MS9555-03 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.260 Inches Maximum
Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.220 Inches Minimum And 0.240 Inches Maximum
Width Between Flats:	0.219 Inches Nominal
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS9555-03 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.