

Description


Overall Length: 3/8", Thread: 1/8-36, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955505
Minimum Qty (MOQ):	20
NSN:	5305-00-448-4707
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9555-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.346 Inches Minimum And 0.386 Inches Maximum
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.230 Inches Nominal
Width Between Flats:	0.219 Inches Nominal
Extended Washer Diameter:	0.312 Inches Nominal
Extended Washer Thickness:	0.030 Inches Nominal
First Diameter From Head:	0.141 Inches Minimum And 0.151 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.062 Inches Minimum And 0.082 Inches Maximum
Internal Drive Style:	W/o Internal Drive
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Externally Relieved Body Diameter Quantity:	1
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.