

P/N MS9555-06

Description

Fastener Length: 1/2", Thread: 8-36, Thread Length: 27/64", MS9555 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS955506

Minimum Qty (MOQ): 10

NSN: 5305-00-171-5523

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS9555-06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.408 Inches Minimum And 0.448 Inches Maximum
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Double Hexagon W/ Hole
Head Height:	0.220 Inches Minimum And 0.240 Inches Maximum
Width Between Flats:	0.219 Inches Nominal
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum
End Item Identification:	W/s: Engine, T700-ge-701c (uh-60/mh-60k/ah-64); Engine, T703-ad-700a/b/c (oh-58d); Engine, Aircraft, J69-t-25 (t-37b); Helicopter, Advance Attack, Ah-1w; Engine, Missile F112-wr-100 (advanced Cruise Missile); Engine, Aircraft, Tf34-ge-100 (a-10); Ah-64-d Long Bow; Helicopter, Electronic Countermeasures, Eh-60a; Hh-60l Medivac; Engine, T700-ge-700 (uh-60 & Eh-60a)
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Screw Material:	Iron Alloy 660
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Special Features:	Without Internal Drive
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS9555-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.