

**Description**

Fastener Length: 1/2", Thread: 8-36, Thread Length: 27/64", MS9555 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS955506
Minimum Qty (MOQ):	10
NSN:	5305-00-171-5523
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS9555-06 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.408 Inches Minimum And 0.448 Inches Maximum
<b>Fastener Length:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/ Hole
<b>Head Height:</b>	0.220 Inches Minimum And 0.240 Inches Maximum
<b>Width Between Flats:</b>	0.219 Inches Nominal
<b>Extended Washer Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Extended Washer Thickness:</b>	0.030 Inches Minimum
<b>End Item Identification:</b>	W/s: Engine, T700-ge-701c (uh-60/mh-60k/ah-64); Engine, T703-ad-700a/b/c (oh-58d); Engine, Aircraft, J69-t-25 (t-37b); Helicopter, Advance Attack, Ah-1w; Engine, Missile F112-wr-100 (advanced Cruise Missile); Engine, Aircraft, Tf34-ge-100 (a-10); Ah-64-d Long Bow; Helicopter, Electronic Countermeasures, Eh-60a; Hh-60l Medivac; Engine, T700-ge-700 (uh-60 & Eh-60a)
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Screw Material:</b>	Iron Alloy 660
<b>Bearing Surface Of Head Surface Finish:</b>	32.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Special Features:</b>	Without Internal Drive
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.