

## Description

Fastener Length: 9/16", Thread: 8-36, Thread Length: 31/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS955507
Minimum Qty (MOQ):	10
NSN:	5305-00-447-6532
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



## P/N MS9555-07 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.470 Inches Minimum And 0.510 Inches Maximum
<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/ Hole
<b>Head Height:</b>	0.220 Inches Minimum And 0.240 Inches Maximum
<b>Width Between Flats:</b>	0.219 Inches Nominal
<b>Extended Washer Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Extended Washer Thickness:</b>	0.030 Inches Minimum
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.