

Description

Fastener Length: 5/8", Thread: 8-36, Thread Length: 35/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955508
Minimum Qty (MOQ):	10
NSN:	5305-00-170-1424
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9555-08 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.533 Inches Minimum And 0.573 Inches Maximum
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Double Hexagon W/ Hole
Head Height:	0.230 Inches Nominal
Width Between Flats:	0.219 Inches Nominal
Extended Washer Diameter:	0.312 Inches Nominal
Extended Washer Thickness:	0.030 Inches Minimum
End Item Identification:	W/s: Engine, Aircraft Tf-34
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.