

P/N MS9555-08

Description

Fastener Length: 5/8", Thread: 8-36, Thread Length: 35/64

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS955508

Minimum Qty (MOQ): 10

NSN: 5305-00-170-1424

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS9555-08 Specifications

| Thread Class: | 3a |
|----------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.533 Inches Minimum And 0.573 Inches Maximum |
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Double Hexagon W/ Hole |
| Head Height: | 0.230 Inches Nominal |
| Width Between Flats: | 0.219 Inches Nominal |
| Extended Washer Diameter: | 0.312 Inches Nominal |
| Extended Washer Thickness: | 0.030 Inches Minimum |
| End Item Identification: | W/s: Engine, Aircraft Tf-34 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 36 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum |
| Screw Material: | Iron Alloy 660 |
| Thread Series Designator: | Unjf |

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS9555-08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS9555-08 and selecting the quantity you