



Military-Fasteners.com

P/N MS9555-10

Description

Fastener Length: 3/4", Thread: 8-36, Thread Length: 39/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955510
Minimum Qty (MOQ):	10
NSN:	5305-01-326-0110
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9555-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.608 Inches Nominal
Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Double Hexagon W/ Hole
Head Height:	0.220 Inches Minimum And 0.240 Inches Maximum
Width Between Flats:	0.208 Inches Minimum And 0.228 Inches Maximum
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Special Features:	Without Internal Drive
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.