

**Description**

Fastener Length: 7/8", Thread: 8-36, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS955512
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-174-8633
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9555-12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.568 Inches Minimum And 0.648 Inches Maximum
<b>Fastener Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/ Hole
<b>Head Height:</b>	0.220 Inches Minimum And 0.240 Inches Maximum
<b>Width Between Flats:</b>	0.219 Inches Nominal
<b>Extended Washer Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Extended Washer Thickness:</b>	0.030 Inches Minimum
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Bearing Surface Of Head Surface Finish:</b>	32.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Special Features:</b>	Without Internal Drive
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9555-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.