

P/N MS9556-05

Description

length: 7/16", thread: 10-32, 12 point, extended washer head, corrosion and heat resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS955605

Minimum Qty (MOQ):

NSN: 5306-00-104-5183

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N MS9556-05 Specifications

Thursd Class.	20
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.346 Inches Minimum And 0.366 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.260 Inches Nominal
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Hardness Rating:	248.0 Brinell Standard Minimum And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9556-05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.