

P/N MS9557-13

Description

length: 15/16", thread: 1/4-28, 12 point, extended washer head, corrosion and heat resistant steel, MS9557 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS955713

Minimum Qty (MOQ): 10

NSN: 5306-00-079-1299

Schedule B: 7318.15.2095

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)





^{*} See page 2 for technical characteristics

P/N MS9557-13 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	0.938 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.300 Inches Nominal
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.128 Inches Minimum And 0.188 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	C8
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9557-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.