

Description

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 47/64", MS9557 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955720
Minimum Qty (MOQ):	10
NSN:	5306-01-056-3506
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9557-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.720 Inches Minimum And 0.740 Inches Maximum
Fastener Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.290 Inches Minimum And 0.310 Inches Maximum
Width Between Flats:	0.311 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.050 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.565 Inches Minimum And 0.625 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9557-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.