

Description

Fastener Length: 1-3/4", Thread: 1/4-28, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS955726 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-00-124-3023 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS9557-26 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.750 Inches Minimum And 0.810 Inches Maximum |
| Fastener Length: | 1.750 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.300 Inches Nominal |
| Width Between Flats: | 0.305 Inches Minimum And 0.313 Inches Maximum |
| Extended Washer Diameter: | 0.438 Inches Nominal |
| Extended Washer Thickness: | 0.060 Inches Minimum And 0.070 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.940 Inches Minimum And 1.000 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall |
| Minimum Yield Strength: | 85000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9557-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.