

Description

Fastener Length: 4-1/4", Thread: 1/4-28, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955746
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-359-4622
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9557-46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	4.250 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.300 Inches Nominal
Width Between Flats:	0.348 Inches Minimum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	3.440 Inches Minimum And 3.500 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731-85 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt12 from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9557-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.