

Description

Fastener Length: 7/8", Thread: 1/4-24, Thread Length: 25/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955810
Minimum Qty (MOQ):	10
NSN:	5306-01-187-0632
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9558-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.767 Inches Minimum And 0.787 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.348 Inches Nominal
Width Between Flats:	0.375 Inches Nominal
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.088 Inches Minimum And 0.108 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.