

Description

Length: 0-63/64", Thread: 1/4-24, Thread Length: 59/64", MS9558 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955812
Minimum Qty (MOQ):	5
NSN:	5306-01-328-6066
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9558-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.865 Inches Minimum And 0.922 Inches Maximum
Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.338 Inches Minimum And 0.358 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Extended Washer Thickness:	0.070 Inches Minimum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.088 Inches Minimum And 0.125 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.