

Description

Length: 0-63/64", Thread: 1/4-24, Thread Length: 59/64", MS9558 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS955812 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-328-6066 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS9558-12 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.865 Inches Minimum And 0.922 Inches Maximum |
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Double Hexagon Extended Washer |
| Head Height: | 0.338 Inches Minimum And 0.358 Inches Maximum |
| Width Between Flats: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Extended Washer Diameter: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Extended Washer Thickness: | 0.070 Inches Minimum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.088 Inches Minimum And 0.125 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.