



Military-Fasteners.com

P/N MS9558-24

## Description

Fastener Length: 1-3/4", Thread: 1/4-24, Thread Length: 59/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS955824                                  |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-443-5877                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS9558-24 Specifications

|  |   |
|--|---|
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.875 Inches Minimum And 0.935 Inches Maximum                                     |
| <b>Fastener Length:</b>                      | 1.750 Inches Nominal  |
| <b>Head Style:</b>                           | Double Hexagon W/hole   |
| <b>Head Height:</b>                          | 0.375 Inches Nominal  |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum                                     |
| <b>Extended Washer Diameter:</b>             | 0.500 Inches Nominal  |
| <b>Extended Washer Thickness:</b>            | 0.070 Inches Minimum And 0.080 Inches Maximum                                     |
| <b>Nominal Thread Diameter:</b>              | 0.312 Inches  |
| <b>Grip Length:</b>                          | 0.815 Inches Minimum And 0.875 Inches Maximum                                     |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Nonstandard Thread Pitch Diameter:</b>    | +0.2797/+0.2824 Inches  |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 130000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                      | 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall |
| <b>Minimum Yield Strength:</b>               | 85000 Pounds Per Square Inch  |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads  |
| <b>Surface Finish:</b>                       | 63.0 Microinches Bearing Surface Of Head  |
| <b>Surface Finish:</b>                       | 63.0 Microinches Grip   |
| <b>Material:</b>                             | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b> | Ams 5735 Assn Std Single Material Response Overall                                |
| <b>Thread Series Designator:</b>             | Uns   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.