

Description

Fastener Length: 2-3/4", Thread: 1/4-24, Thread Length: 59/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS955832 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-483-3659 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS9558-32 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.875 Inches Minimum And 0.935 Inches Maximum |
| Fastener Length: | 2.750 Inches Nominal |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.348 Inches Nominal |
| Width Between Flats: | 0.375 Inches Nominal |
| Extended Washer Diameter: | 0.500 Inches Nominal |
| Extended Washer Thickness: | 0.070 Inches Minimum |
| Grip Diameter: | 0.280 Inches Minimum And 0.290 Inches Maximum |
| End Item Identification: | 1055-01-450-4243 |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.815 Inches Minimum And 1.875 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 85000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731-85 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.