

Description

Fastener Length: 2-63/64", Thread: 5/16-24, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS955834
Minimum Qty (MOQ):	1000 EA
NSN:	5306-01-529-6426
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS9558-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.925 Inches Minimum And 1.885 Inches Maximum
Fastener Length:	2.990 Inches Minimum And 3.010 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.338 Inches Minimum And 0.358 Inches Maximum
Width Between Flats:	0.3750 Inches Nominal
Extended Washer Diameter:	0.490 Inches Minimum And 0.510 Inches Maximum
Extended Washer Thickness:	0.166 Inches Minimum And 0.186 Inches Maximum
Nominal Thread Diameter:	0.3125 Inches
Thread Quantity Per Inch:	24
Surface Finish:	125.0 Microinches Overall
Special Features:	130 Ksi Minmum;6.58 Approximate Mass Pound Per 100
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.