

**Description**

Fastener Length: 2-63/64", Thread: 5/16-24, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS955834
Minimum Qty (MOQ):	1000 EA
NSN:	5306-01-529-6426
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N MS9558-34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.925 Inches Minimum And 1.885 Inches Maximum
<b>Fastener Length:</b>	2.990 Inches Minimum And 3.010 Inches Maximum
<b>Head Style:</b>	Double Hexagon Extended Washer
<b>Head Height:</b>	0.338 Inches Minimum And 0.358 Inches Maximum
<b>Width Between Flats:</b>	0.3750 Inches Nominal
<b>Extended Washer Diameter:</b>	0.490 Inches Minimum And 0.510 Inches Maximum
<b>Extended Washer Thickness:</b>	0.166 Inches Minimum And 0.186 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.3125 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Surface Finish:</b>	125.0 Microinches Overall
<b>Special Features:</b>	130 Ksi Minmum;6.58 Approximate Mass Pound Per 100
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9558-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.