

## P/N MS9559-08

## **Description**

Fastener Length: 7/8", Thread: 3/8-24, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS955908

Minimum Qty (MOQ): 5

NSN: 5306-01-103-1151

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# P/N MS9559-08 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.777 Inches Nominal
Fastener Length:	0.875 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.437 Inches Nominal
Extended Washer Diameter:	0.562 Inches Nominal
Extended Washer Thickness:	0.090 Inches Minimum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.088 Inches Minimum And 0.108 Inches Maximum
Thread Quantity Per Inch:	24
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms9559 Government Standard

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9559-08">https://military-fasteners.com/bolts/machine+bolts/MS9559-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS9559-08">https://military-fasteners.com/bolts/machine+bolts/MS9559-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS9559-08">https://military-fasteners.com/bolts/machine+bolts/MS9559-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/MS9559-08">https://military-fasteners.com/bolts/machine+bolts/MS9559-08</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/machine+bolts/ms9559-08">https://military-fasteners.com/bolts/ms9559-08</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/ms9559-08">https://military-fasteners.com/bolts/ms9559-08</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/ms9559-08">https://military-fasteners.com/bolts/ms9559-08</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/ms9559-08">https://military-fasteners.com/bolts/ms959-08</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/ms959-08">https://military-fasteners.com/bolts/ms959-08</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/ms959-08">https://military-fasteners.com/bolts/ms959-08</a> and selecting the property of the p