



Military-Fasteners.com

P/N MS9564-03

Description

Fastener Length: 5/16", Hole Diameter: 3/64", Thread: 8-36, Thread Length: 15/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS956403                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-132-5277                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS9564-03 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                               | 3a  |
| <b>Thread Direction:</b>                           | Right-hand  |
| <b>Thread Length:</b>                              | 0.220 Inches Minimum And 0.260 Inches Maximum       |
| <b>Fastener Length:</b>                            | 0.302 Inches Minimum And 0.322 Inches Maximum       |
| <b>Head Style:</b>                                 | Double Hexagon W/ Hole                              |
| <b>Head Height:</b>                                | 0.220 Inches Minimum And 0.240 Inches Maximum       |
| <b>Width Between Flats:</b>                        | 0.219 Inches Nominal                                |
| <b>Extended Washer Diameter:</b>                   | 0.302 Inches Minimum And 0.322 Inches Maximum       |
| <b>Extended Washer Thickness:</b>                  | 0.030 Inches Minimum                                |
| <b>Hole Diameter:</b>                              | 0.047 Inches Minimum And 0.060 Inches Maximum       |
| <b>Nominal Thread Diameter:</b>                    | 0.164 Inches  |
| <b>Hole Quantity:</b>                              | 4   |
| <b>Thread Quantity Per Inch:</b>                   | 36  |
| <b>Minimum Tensile Strength:</b>                   | 130000 Pounds Per Square Inch                       |
| <b>Hardness Rating:</b>                            | 24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum |
| <b>Screw Material:</b>                             | Iron Alloy 660                                      |
| <b>Screw Material Document And Classification:</b> | Ams5731 Assn Std Single Material Response           |
| <b>Head Hole Configuration Style:</b>              | Double Hexagon Longitudinal Hole                    |
| <b>Thread Series Designator:</b>                   | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9564-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.