



Military-Fasteners.com

P/N MS9564-03

Description

Fastener Length: 5/16", Hole Diameter: 3/64", Thread: 8-36, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS956403
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-132-5277
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9564-03 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.220 Inches Minimum And 0.260 Inches Maximum
Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Double Hexagon W/ Hole
Head Height:	0.220 Inches Minimum And 0.240 Inches Maximum
Width Between Flats:	0.219 Inches Nominal
Extended Washer Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Thickness:	0.030 Inches Minimum
Hole Diameter:	0.047 Inches Minimum And 0.060 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	4
Thread Quantity Per Inch:	36
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response
Head Hole Configuration Style:	Double Hexagon Longitudinal Hole
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9564-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.