

Description

length: 7/16", thread: 10-32, drilled, extended washer head, corrosion and heat resistant steel, MS9565 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS956505 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-775-6235 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS9565-05 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.336 Inches Minimum And 0.376 Inches Maximum |
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.250 Inches Minimum And 0.270 Inches Maximum |
| Width Between Flats: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Extended Washer Diameter: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Extended Washer Thickness: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.072 Inches Minimum And 0.092 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Hole Configuration Style: | Double Hexagon Longitudinal Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9565-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.