



★ FASTENERS

Military-Fasteners.com

P/N MS9565-06

Description

length: 1/2", thread: 10-32, drilled head, corrosion and heat resistant steel, MS9565 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS956506
Minimum Qty (MOQ):	10
NSN:	5306-00-775-6243
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9565-06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.398 Inches Minimum And 0.428 Inches Maximum
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.250 Inches Minimum And 0.270 Inches Maximum
Width Between Flats:	0.240 Inches Minimum And 0.260 Inches Maximum
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9565-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.