

Description

Fastener Length: 1-3/4", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS956526
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-116-6608
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9565-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.680 Inches Minimum And 0.740 Inches Maximum
Fastener Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.250 Inches Minimum And 0.270 Inches Maximum
Width Between Flats:	0.250 Inches Nominal
Extended Washer Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum
Hole Diameter:	0.037 Inches Minimum And 0.057 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.020 Inches Minimum And 1.060 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9565-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.