

Description

Fastener Length: 1-3/16", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 1-3/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS956813
Minimum Qty (MOQ):	5
NSN:	5306-00-103-9753
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9568-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Minimum And 1.060 Inches Maximum
Fastener Length:	1.188 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.388 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.562 Inches Nominal
Extended Washer Thickness:	0.090 Inches Minimum And 0.100 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.128 Inches Minimum And 0.188 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9568-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.