

P/N MS9574-13

Description

Fastener Length: 15/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS957413
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-259-6315
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9574-13 Specifications

Thread Direction: Thread Length: 0.620 Inches Minimum And 0.700 Inches Maximum Fastener Length: 0.928 Inches Minimum And 0.948 Inches Maximum Head Style: Double Hexagon W/hole Head Height: 0.250 Inches Minimum And 0.270 Inches Maximum Width Between Flats: 0.250 Inches Nominal Extended Washer Diameter: 0.365 Inches Minimum And 0.385 Inches Maximum Extended Washer Thickness: 0.040 Inches Minimum Hole Diameter: 0.037 Inches Minimum And 0.057 Inches Maximum
Thread Length: Fastener Length: 0.620 Inches Minimum And 0.700 Inches Maximum 0.928 Inches Minimum And 0.948 Inches Maximum Double Hexagon W/hole Head Height: 0.250 Inches Minimum And 0.270 Inches Maximum Width Between Flats: 0.250 Inches Nominal Extended Washer Diameter: 0.365 Inches Minimum And 0.385 Inches Maximum 0.040 Inches Minimum
Head Style: Head Height: O.250 Inches Minimum And 0.270 Inches Maximum Width Between Flats: O.250 Inches Nominal Extended Washer Diameter: O.365 Inches Minimum And 0.385 Inches Maximum O.040 Inches Minimum
Head Height: Width Between Flats: 0.250 Inches Minimum And 0.270 Inches Maximum 0.250 Inches Nominal 0.365 Inches Minimum And 0.385 Inches Maximum 0.040 Inches Minimum 0.040 Inches Minimum
Width Between Flats: 0.250 Inches Nominal 0.365 Inches Minimum And 0.385 Inches Maximum Extended Washer Thickness: 0.040 Inches Minimum
Extended Washer Diameter: 0.365 Inches Minimum And 0.385 Inches Maximum 0.040 Inches Minimum
Extended Washer Thickness: 0.040 Inches Minimum
Hole Diameter: 0.037 Inches Minimum And 0.057 Inches Maximum
Nominal Thread Diameter: 0.190 Inches
Grip Length: 0.248 Inches Minimum And 0.308 Inches Maximum
Hole Quantity: 4
Hole Type: Drilled
Features Provided: Finished Head
Thread Quantity Per Inch: 32
Minimum Tensile Strength: 130000 Pounds Per Square Inch
Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength: 85000 Pounds Per Square Inch
Hole Configuration Style: Double Hexagon Longitudinal Hole
Surface Finish: 32.0 Microinches Bearing Surface Of Head
Surface Finish: 32.0 Microinches Grip
Surface Finish: 32.0 Microinches Threads
Material: Iron Alloy 660 Overall
Material Document And Classification: Ams5731 Assn Std Single Material Response Overall
Precious Material And Location: Overall Silver
Precious Material: Silver
Surface Treatment: Silver Overall
Surface Treatment Document And Classification: Ams2411 Assn Std Single Treatment Response Overall
Thread Series Designator: Unjf

How to Order Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9574-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.