

# P/N MS9574-13

## **Description**

Fastener Length: 15/16", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model:	MS957413
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-259-6315
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9574-13 Specifications

Thread Direction:  Thread Length:  0.620 Inches Minimum And 0.700 Inches Maximum  0.928 Inches Minimum And 0.948 Inches Maximum  Head Style:  Double Hexagon W/hole  Head Height:  0.250 Inches Minimum And 0.270 Inches Maximum  Width Between Flats:  0.250 Inches Nominal  Extended Washer Diameter:  0.365 Inches Minimum And 0.385 Inches Maximum  Extended Washer Thickness:  0.040 Inches Minimum
Thread Length:  0.620 Inches Minimum And 0.700 Inches Maximum  0.928 Inches Minimum And 0.948 Inches Maximum  Head Style:  Double Hexagon W/hole  Head Height:  0.250 Inches Minimum And 0.270 Inches Maximum  Width Between Flats:  0.250 Inches Nominal  Extended Washer Diameter:  0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:  Head Height:  0.250 Inches Minimum And 0.270 Inches Maximum  Width Between Flats:  0.250 Inches Nominal  0.250 Inches Nominal  Extended Washer Diameter:  0.365 Inches Minimum And 0.385 Inches Maximum
Head Height:  0.250 Inches Minimum And 0.270 Inches Maximum  0.250 Inches Nominal  0.250 Inches Nominal  0.365 Inches Minimum And 0.385 Inches Maximum
Width Between Flats:  0.250 Inches Nominal  Extended Washer Diameter:  0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Diameter: 0.365 Inches Minimum And 0.385 Inches Maximum
Extended Washer Thickness: 0.040 Inches Minimum
Hole Diameter: 0.037 Inches Minimum And 0.057 Inches Maximum
Nominal Thread Diameter: 0.190 Inches
Grip Length: 0.248 Inches Minimum And 0.308 Inches Maximum
Hole Quantity: 4
Hole Type: Drilled
Features Provided: Finished Head
Thread Quantity Per Inch: 32
Minimum Tensile Strength: 130000 Pounds Per Square Inch
Hardness Rating: 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength: 85000 Pounds Per Square Inch
Hole Configuration Style: Double Hexagon Longitudinal Hole
Surface Finish: 32.0 Microinches Bearing Surface Of Head
Surface Finish: 32.0 Microinches Grip
Surface Finish: 32.0 Microinches Threads
Material: Iron Alloy 660 Overall
Material Document And Classification: Ams5731 Assn Std Single Material Response Overall
Precious Material And Location: Overall Silver
Precious Material: Silver
Surface Treatment: Silver Overall
Surface Treatment Document And Classification: Ams2411 Assn Std Single Treatment Response Overall
Thread Series Designator: Unjf

# **How to Order** Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/MS9574-13">https://military-fasteners.com/bolts/machine+bolts/MS9574-13</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.