



Military-Fasteners.com

P/N MS9574-14

## Description

Fastener Length: 1", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS957414                                  |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-00-124-3021                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N MS9574-14 Specifications

|  |   |
|--|---|
| Thread Class:                                  | 3a  |
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 0.630 Inches Minimum And 0.690 Inches Maximum                                     |
| Fastener Length:                               | 1.000 Inches Nominal  |
| Head Style:                                    | Double Hexagon W/hole   |
| Head Height:                                   | 0.260 Inches Nominal  |
| Width Between Flats:                           | 0.243 Inches Minimum And 0.251 Inches Maximum                                     |
| Extended Washer Diameter:                      | 0.375 Inches Nominal  |
| Extended Washer Thickness:                     | 0.040 Inches Minimum And 0.050 Inches Maximum                                     |
| Hole Diameter:                                 | 0.047 Inches Nominal  |
| Nominal Thread Diameter:                       | 0.190 Inches  |
| Grip Length:                                   | 0.310 Inches Minimum And 0.370 Inches Maximum                                     |
| Hole Quantity:                                 | 4   |
| Hole Type:                                     | Drilled   |
| Features Provided:                             | Finished Head   |
| Thread Quantity Per Inch:                      | 32  |
| Minimum Tensile Strength:                      | 130000 Pounds Per Square Inch   |
| Hardness Rating:                               | 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall |
| Minimum Yield Strength:                        | 85000 Pounds Per Square Inch  |
| Hole Configuration Style:                      | Round   |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head  |
| Surface Finish:                                | 32.0 Microinches Grip   |
| Surface Finish:                                | 32.0 Microinches Threads  |
| Material:                                      | Iron Alloy 660 Overall  |
| Material Document And Classification:          | Ams 5731 Assn Std Single Material Response Overall                                |
| Precious Material:                             | Silver  |
| Surface Treatment:                             | Silver Overall  |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall                               |
| Thread Series Designator:                      | Unjf  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9574-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.