

Description

Fastener Length: 2-1/2", Hole Diameter: 1/16", Thread: 1/4-28, Thread Length: 51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS957532
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-566-6682
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9575-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.790 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	2.500 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.300 Inches Nominal
Width Between Flats:	0.312 Inches Nominal
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum
Hole Diameter:	0.070 Inches Nominal
End Item Identification:	C-5 Aircraft
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Part Name Assigned By Controlling Agency:	Bolt
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9575-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.