

P/N MS9576-06

Description

Fastener Length: 5/8", Hole Diameter: 1/16", Thread: 5/16-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS957606
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-222-3283
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9576-06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.542 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.348 Inches Nominal
Width Between Flats:	0.375 Inches Nominal
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.070 Inches Minimum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.3125 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hole Configuration Style:	Round Longitudinal Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Precious Material And Location:	Overall Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2411 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9576-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.