

**Description**

diameter: 1/4", corrosion resistant steel, keyed, MS9581 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS958110
Minimum Qty (MOQ):	25
NSN:	5310-00-471-9105
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N MS9581-10 Specifications

<b>Hole Diameter:</b>	0.250 Inches Nominal
<b>Outside Diameter:</b>	0.440 Inches Minimum And 0.450 Inches Maximum
<b>External Prebent Key Length:</b>	0.110 Inches Minimum And 0.115 Inches Maximum
<b>External Tapered Key Width:</b>	0.250 Inches Minimum And 0.260 Inches Maximum
<b>External Prebent Key Width:</b>	0.110 Inches Minimum And 0.115 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.265 Inches Minimum And 0.275 Inches Maximum
<b>Material Thickness:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Angle Between External Keys:</b>	58.0 Degrees Minimum And 62.0 Degrees Maximum
<b>External Prebent Key Angle:</b>	15.0 Degrees Nominal
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams 5510 Assn Std Single Material Response Overall
<b>Style Designator:</b>	90 Degree Locking Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9581-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.