

**Description**

diameter: 3/16", corrosion resistant steel, keyed, 270 degree locking, MS9582 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS958209
Minimum Qty (MOQ):	20
NSN:	5310-00-143-6177
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS9582-09 Specifications

<b>Hole Diameter:</b>	0.190 Inches Nominal
<b>Outside Diameter:</b>	0.370 Inches Minimum And 0.380 Inches Maximum
<b>External Prebent Key Length:</b>	0.095 Inches Minimum And 0.105 Inches Maximum
<b>External Tapered Key Width:</b>	0.200 Inches Minimum And 0.210 Inches Maximum
<b>External Prebent Key Width:</b>	0.110 Inches Minimum And 0.115 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.221 Inches Minimum And 0.231 Inches Maximum
<b>Material Thickness:</b>	0.019 Inches Minimum And 0.025 Inches Maximum
<b>Angle Between External Keys:</b>	58.0 Degrees Minimum And 62.0 Degrees Maximum
<b>External Prebent Key Angle:</b>	15.0 Degrees Nominal
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams5510 Assn Std Single Material Response Overall
<b>Style Designator:</b>	270 Degree Locking Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9582-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.