

Description

diameter: 3/16", corrosion resistant steel, keyed, 270 degree locking, MS9582 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS958209
Minimum Qty (MOQ):	20
NSN:	5310-00-143-6177
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS9582-09 Specifications

Hole Diameter:	0.190 Inches Nominal
Outside Diameter:	0.370 Inches Minimum And 0.380 Inches Maximum
External Prebent Key Length:	0.095 Inches Minimum And 0.105 Inches Maximum
External Tapered Key Width:	0.200 Inches Minimum And 0.210 Inches Maximum
External Prebent Key Width:	0.110 Inches Minimum And 0.115 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.221 Inches Minimum And 0.231 Inches Maximum
Material Thickness:	0.019 Inches Minimum And 0.025 Inches Maximum
Angle Between External Keys:	58.0 Degrees Minimum And 62.0 Degrees Maximum
External Prebent Key Angle:	15.0 Degrees Nominal
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams5510 Assn Std Single Material Response Overall
Style Designator:	270 Degree Locking Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9582-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.