

P/N MS9582-10

Description

diameter: 1/4" - corrosion resistant steel keyed washer - 270ÃÂ \square Â $^\circ$ locking

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS958210
Minimum Qty (MOQ):	10
NSN:	5310-00-121-8014
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



^{*} See page 2 for technical characteristics

P/N MS9582-10 Specifications

Outside Diameter:	0.255 Inches Minimum And 0.260 Inches Maximum
External Prebent Key Length:	0.100 Inches Minimum And 0.110 Inches Maximum
External Tapered Key Width:	0.250 Inches Minimum And 0.260 Inches Maximum
External Prebent Key Width:	0.110 Inches Minimum And 0.115 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.265 Inches Minimum And 0.275 Inches Maximum
Material Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Angle Between External Keys:	58.0 Degrees Minimum And 62.0 Degrees Maximum
External Prebent Key Angle:	15.0 Degrees Nominal
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall
Style Designator:	270 Degree Locking Key

How to Order

Order this key washer from our inventory online by visiting https://military-fasteners.com/washers/key+washers/MS9582-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.