

Description

diameter: 1/4" - corrosion resistant steel keyed washer - 270° locking

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS958210 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-121-8014 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS9582-10 Specifications

| | |
|---|--|
| Outside Diameter: | 0.255 Inches Minimum And 0.260 Inches Maximum |
| External Prebent Key Length: | 0.100 Inches Minimum And 0.110 Inches Maximum |
| External Tapered Key Width: | 0.250 Inches Minimum And 0.260 Inches Maximum |
| External Prebent Key Width: | 0.110 Inches Minimum And 0.115 Inches Maximum |
| Distance From Centerline To Inside Of Prebent Key: | 0.265 Inches Minimum And 0.275 Inches Maximum |
| Material Thickness: | 0.028 Inches Minimum And 0.036 Inches Maximum |
| Angle Between External Keys: | 58.0 Degrees Minimum And 62.0 Degrees Maximum |
| External Prebent Key Angle: | 15.0 Degrees Nominal |
| Material: | Steel Comp 321 Overall |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Overall |
| Style Designator: | 270 Degree Locking Key |

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9582-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.