

Description

diameter: 5/16" - corrosion resistant steel keyed washer - 270° locking

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS958211
Minimum Qty (MOQ):	10
NSN:	5310-01-343-4226
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N MS9582-11 Specifications

Hole Diameter:	0.320 Inches Minimum And 0.325 Inches Maximum
Outside Diameter:	0.495 Inches Minimum And 0.505 Inches Maximum
External Prebent Key Length:	0.050 Inches Nominal
External Tapered Key Width:	0.280 Inches Minimum And 0.290 Inches Maximum
External Prebent Key Width:	0.140 Inches Minimum And 0.145 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.100 Inches Minimum And 0.110 Inches Maximum
Material Thickness:	0.028 Inches Minimum And 0.036 Inches Maximum
Angle Between External Keys:	58.0 Degrees Minimum And 62.0 Degrees Maximum
External Prebent Key Angle:	15.0 Degrees Nominal
Surface Finish:	32.0 Microinches Top
Heat Treatment:	Stress Relieved
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall
Style Designator:	270 Degree Locking Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9582-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.