

**Description**

diameter: 5/16" - corrosion resistant steel keyed washer - 270° locking

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS958211
Minimum Qty (MOQ):	10
NSN:	5310-01-343-4226
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS9582-11 Specifications

<b>Hole Diameter:</b>	0.320 Inches Minimum And 0.325 Inches Maximum
<b>Outside Diameter:</b>	0.495 Inches Minimum And 0.505 Inches Maximum
<b>External Prebent Key Length:</b>	0.050 Inches Nominal
<b>External Tapered Key Width:</b>	0.280 Inches Minimum And 0.290 Inches Maximum
<b>External Prebent Key Width:</b>	0.140 Inches Minimum And 0.145 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.100 Inches Minimum And 0.110 Inches Maximum
<b>Material Thickness:</b>	0.028 Inches Minimum And 0.036 Inches Maximum
<b>Angle Between External Keys:</b>	58.0 Degrees Minimum And 62.0 Degrees Maximum
<b>External Prebent Key Angle:</b>	15.0 Degrees Nominal
<b>Surface Finish:</b>	32.0 Microinches Top
<b>Heat Treatment:</b>	Stress Relieved
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams 5510 Assn Std Single Material Response Overall
<b>Style Designator:</b>	270 Degree Locking Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9582-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.