

P/N MS9592-006

Military-Fasteners.com

Description

Angle Bracket part number

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS9592006
Minimum Qty (MOQ):	20
NSN:	5340-00-165-1881
Schedule B:	8302.42.3065
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N MS9592-006 Specifications

First Leg Length:	0.633 Inches Minimum And 0.643 Inches Maximum
Second Leg Length:	0.695 Inches Minimum And 0.705 Inches Maximum
Second Leg Width:	0.500 Inches Nominal
First Leg Hole Diameter:	0.200 Inches Minimum And 0.210 Inches Maximum
Second Leg Hole Diameter:	0.200 Inches Minimum And 0.210 Inches Maximum
Second Leg Distance From Edge To Hole Center Along Width:	0.210 Inches Minimum And 0.245 Inches Maximum
Second Leg Distance From Edge To Hole Center Along Length:	0.195 Inches Minimum And 0.205 Inches Maximum
First Leg Thickness:	0.056 Inches Minimum And 0.068 Inches Maximum
Second Leg Thickness:	0.056 Inches Minimum And 0.068 Inches Maximum
First Leg Width:	0.500 Inches Nominal
First Leg Distance From Edge To Hole Center Along Width:	0.245 Inches Minimum And 0.255 Inches Maximum
First Leg Distance From Edge To Hole Center Along Length:	0.195 Inches Minimum And 0.205 Inches Maximum
First Leg End Radius:	0.500 Inches Nominal
Second Leg End Radius:	0.500 Inches Nominal
First Leg Style:	End Radius
First Leg Hole Arrangement Style:	One Hole
Second Leg Style:	End Radius
Second Leg Hole Arrangement Style:	One Hole
Second Leg Relationship To First Leg:	Not Identical
First Leg Angle:	90.0 Degrees Nominal
Material:	Steel Comp 321
Material Document And Classification:	Ams 5510 Assn Std Single Material Response
Style Designator:	Angle

How to Order

Order this angle bracket from our inventory online by visiting <u>https://military-fasteners.com/shop+supplies/angle+brackets/MS9592-006</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.