

Description

Bracket part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS9592220
Minimum Qty (MOQ):	20 EA
NSN:	5340-01-454-9235
Schedule B:	8302.42.3065
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS9592-220 Specifications

Mounting Hole Type:	Plain
First Leg Length:	0.9450 Inches Nominal
Second Leg Length:	1.5740 Inches Nominal
Second Leg Width:	0.5000 Inches Nominal
First Leg Hole Diameter:	0.2000 Inches Minimum And 0.2100 Inches Maximum
Second Leg Hole Diameter:	0.2000 Inches Minimum And 0.2100 Inches Maximum
Second Leg Distance From Edge To Hole Center Along Width:	0.2450 Inches Minimum And 0.2550 Inches Maximum
Second Leg Distance From Edge To Hole Center Along Length:	0.1950 Inches Minimum And 0.2050 Inches Maximum
First Leg Thickness:	0.0560 Inches Minimum And 0.0680 Inches Maximum
Second Leg Thickness:	0.0560 Inches Minimum And 0.0680 Inches Maximum
First Leg Width:	0.5000 Inches Nominal
First Leg Distance From Edge To Hole Center Along Width:	0.2450 Inches Minimum And 0.2550 Inches Maximum
First Leg Distance From Edge To Hole Center Along Length:	0.1950 Inches Minimum And 0.2050 Inches Maximum
First Leg End Radius:	0.5000 Inches Nominal
Second Leg End Radius:	0.5000 Inches Nominal
First Leg Style:	End Radius
First Leg Hole Arrangement Style:	One Hole
Second Leg Style:	End Radius
Second Leg Hole Arrangement Style:	One Hole
Second Leg Relationship To First Leg:	Not Identical
First Leg Angle:	90.0 Radians Nominal
Material:	Steel Comp 321
Material Document And Classification:	Ams-5510 Assn Std Single Material Response
Style Designator:	Angle

How to Order

Order this bracket from our inventory online by visiting <https://military-fasteners.com/shop+supplies/angle+brackets/MS9592-220> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.