

Description

Bracket part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS9592264
Minimum Qty (MOQ):	15 EA
NSN:	5340-01-482-3262
Schedule B:	8302.42.3065
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS9592-264 Specifications

First Leg Length:	1.820 Inches Minimum And 1.830 Inches Maximum
Second Leg Length:	1.007 Inches Minimum And 1.017 Inches Maximum
Second Leg Width:	0.500 Inches Nominal
First Leg Hole Diameter:	0.200 Inches Minimum And 0.210 Inches Maximum
Second Leg Hole Diameter:	0.200 Inches Minimum And 0.210 Inches Maximum
Second Leg Distance From Edge To Hole Center Along Width:	0.245 Inches Minimum And 0.255 Inches Maximum
Second Leg Distance From Edge To Hole Center Along Length:	0.195 Inches Minimum And 0.205 Inches Maximum
First Leg Thickness:	0.056 Inches Minimum And 0.068 Inches Maximum
Second Leg Thickness:	0.056 Inches Minimum And 0.068 Inches Maximum
First Leg Width:	0.500 Inches Nominal
First Leg Distance From Edge To Hole Center Along Width:	0.245 Inches Minimum And 0.255 Inches Maximum
First Leg Distance From Edge To Hole Center Along Length:	0.195 Inches Minimum And 0.205 Inches Maximum
First Leg End Radius:	0.500 Inches Nominal
Second Leg End Radius:	0.500 Inches Nominal
First Leg Style:	End Radius
First Leg Hole Arrangement Style:	One Hole
Second Leg Relationship To First Leg:	Identical
First Leg Angle:	85.0 Degrees Minimum And 95.0 Degrees Maximum
Special Features:	0.190 Bolt
Material:	Steel Corrosion Resisting
Material Document And Classification:	Ams 5510 Assn Std Single Material Response
Style Designator:	Angle

How to Order

Order this bracket from our inventory online by visiting <https://military-fasteners.com/shop+supplies/angle+brackets/MS9592-264> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.