

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS967611
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-253-8268
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9676-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Minimum And 0.700 Inches Maximum
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Double Hexagon Extended Washer
Head Height:	0.279 Inches Minimum And 0.299 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.370 Inches Minimum And 0.375 Inches Maximum
Extended Washer Thickness:	0.072 Inches Minimum And 0.092 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.122 Inches Minimum And 0.182 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9676-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.