

Description

Fastener Length: 11/16", Thread: 10-32, Thread Length: 39/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS969609
Minimum Qty (MOQ):	5
NSN:	5306-00-432-4139
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS9696-09 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.596 Inches Minimum And 0.616 Inches Maximum
Fastener Length:	0.688 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.258 Inches Nominal
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.375 Inches Nominal
Extended Washer Thickness:	0.040 Inches Minimum And 0.050 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	175000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 44.0 Rockwell C Maximum Overall
Minimum Yield Strength:	115000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Nickel Alloy Overall
Material Document And Classification:	Ams 5708 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9696-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.