

**Description**

Fastener Length: 1-", Thread: 1/4-24, Thread Length: 29/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | MS969812         |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5306-01-495-3621 |
| Schedule B:        | 7508.90.5000     |
| ECCN:              | EAR99            |



## P/N MS9698-12 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.875 Inches Minimum And 0.912 Inches Maximum                       |
| <b>Fastener Length:</b>                      | 1.000 Inches Nominal  |
| <b>Head Style:</b>                           | Double Hexagon W/hole   |
| <b>Head Height:</b>                          | 0.338 Inches Nominal  |
| <b>Width Between Flats:</b>                  | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>             | 0.500 Inches Nominal  |
| <b>Extended Washer Thickness:</b>            | 0.070 Inches Minimum And 0.080 Inches Maximum                       |
| <b>End Item Identification:</b>              | F-119   |
| <b>Nominal Thread Diameter:</b>              | 0.312 Inches  |
| <b>Grip Length:</b>                          | 0.088 Inches Minimum And 0.125 Inches Maximum                       |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 32.0 Rockwell C Minimum Overall And 42.0 Rockwell C Maximum Overall |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads  |
| <b>Material:</b>                             | Nickel Alloy Overall  |
| <b>Material Document And Classification:</b> | Ams 5708 Assn Std Single Material Response Overall                  |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9698-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.